

# MAG540

# MAG540 RDK









HIGH-PERFORMANCE LINUX SET-TOP BOXES  
POWERED BY AN AMLOGIC CHIPSET



**MAG540/540w3 RDK** are high-performance 4K and HEVC-enabled Linux set-top boxes intended for operators. The ARM Cortex-A35 quad-core CPU with a new Amlogic S905Y4 chipset ensures this model is more powerful than the previous generation devices. MAG540/540w3 RDK supports all the latest codecs, including H.265 and Dolby Digital Plus™.

On request, we can integrate the set-top box with middleware and DRM/CAS. Operators that used legacy MAG models can quickly integrate the device using the API. The set-top box features two USB ports and offers 100 Mbps Ethernet connectivity, while MAG540w3 RDK also supports wireless connections.

## KEY FEATURES

-  4K and HEVC Support
-  4x ARM Cortex-A35
-  Amlogic S905Y4-B
-  2 GB RAM / 16 GB eMMC
-  Qubic design
-  Linux OS
-  16 500 DMIPS
-  Built-in Wi-Fi module\*

\*only in MAG540w3 RDK

## SPECIFICATIONS

### HARDWARE

Chipset	Amlogic S905Y4-B, 16 500 DMIPS
Processor	ARM Cortex-A35 Quad-Core, 2 000 MHz
RAM / Flash	2 GB / 16 GB eMMC
GPU	ARM G31 MP2, 850 MHz. Supports OpenGL ES 3.2, Vulkan 1.1, and OpenCL 2.0

### AUDIO AND VIDEO

Audio codecs	MPEG L1/L2/L3I, AAC-LC, HE AAC V1/V2, APE, FLAC, Dolby Digital Plus™
Video modes	PAL, NTSC, 576p, 720p, 1080p, 1080i, 2160p
Video codecs	MPEG1/2 MP@HL, MPEG4 part 2 (ASP), AV1, MJPEG streams, H.265 Main/Main 10@L5.1 High 2160p@60 fps (optional), H.264 AVC High@L5.1 2160p@30 fps, XviD, 3D video support
Video containers	TS, AVI, MPEG, MP4, MOV, MKV, M2TS, VOB
Image formats	JPEG, PNG, BMP, RAW
Subtitles	DVB, PGS, SRT, SSA/ASS, SUB, Teletext subs, WebVtt, Closed captions
Playlist formats	M3U, M3U8, PLS, CUE

### SOFTWARE AND CAS/DRM

OS	Linux 5.4
DRM/CAS	Widevine (optional)
MW/UI	Embedded launcher which allows to run video applications: Comcast lightning apps and Youtube. Integration with operator's applications, customization or complete replacement of rootfs image is also available. Supports STB lock for Operator's signing key.

### OTHER INTERFACES

Digital AV	HDMI 2.1
Ethernet	100 Mbps
USB	USB 2.0 x 2
Wi-Fi	Built-in 2T2R ac (MAG540w3 RDK only)

### POWER

PSU	DC 5V, 2A
-----	-----------

### PHYSICAL CHARACTERISTICS

Width/depth/ height	120 x 78 x 21 mm
Weight	110 g

Side panel



Back panel

